



## VH3208 INTRODUCTION

The VH3208 is a passive 3-way monitor.

The dual bass driver design and the 3" softdome ensures that the VH3208 has the benefit of unsurpassed clarity in the mid-range together with a solid LF response. The exceptional quality of the passive crossover has been designed to be free of unnecessary complexity ensuring the VH3208 is comfortable to drive from a single channel of a professional grade amplifier. Configurations include as stand-alone, soffit mount or as part of a large freestanding system when partnered with the QSB112 subs. The recommended amplification is to be capable of between 200W and 700W and typically this product is partnered with our AP950-2 or AP1550-2 amplifier or optionally with the APD1000-4 when sold as part of a freestanding solution including subwoofers.





## TECHNICAL SPECIFICATION

- Dimensions: 485(w) x 612(h) x 324(d) mm / 19"(w) x 24"(h) x 12.5"(d)
- Weight: 38kg / 83.5 lb
- Drivers: Bass cone – 2 x 200mm (8")
- Mid frequency soft dome – 1 x 76 mm (3")
- High Frequency soft dome – 1 x 28 mm (1 1/8th")
- Max SPL: 112dB continuous pink noise @ 1m Leq 1 minute.  
Peak per pair pink noise @ 1m Leq 1 minute 117.5dB
- Frequency Response: 40Hz-20kHz  $\pm$  2dB & 37Hz -6dB
- Connector: Single pair binding posts
- Impedance: 8 ohms
- Sensitivity: 92dB @ 1m
- Recommended Power Amplifier: 200 to 700W RMS, AP950-2 or AP1550-2

### WARRANTY

All Qusted products come with a five year manufacture warranty

